

PSV PEPPE, PSV PEPPE

Instrument: TRZ-0054/01-09

Data format: 16 byte

Full scale [mV]: n.a.

Start recording: 07/09/17 10:45:46 End recording: 07/09/17 11:05:47

Channel labels: NORTH SOUTH; EAST WEST; UP DOWN

GPS data not available

Trace length: 0h20'00". Analyzed 70% trace (manual window selection)

Sampling rate: 128 Hz


Window size: 20 s

Smoothing type: Triangular window


Smoothing: 10%

HORIZONTAL TO VERTICAL SPECTRAL RATIO


Max. H/V at 31.88 ± 3.27 Hz. (In the range 0.0 - 64.0 Hz).




H/V TIME HISTORY



DIRECTIONAL H/V



SINGLE COMPONENT SPECTRA



[According to the SESAME, 2005 guidelines. **Please read carefully the *Grilla* manual before interpreting the following tables.**]

Max. H/V at 31.88 ± 3.27 Hz (in the range 0.0 - 64.0 Hz).

Criteria for a reliable H/V curve

[All 3 should be fulfilled]

| | | | |
|--|------------------------------|----|--|
| $f_0 > 10 / L_w$ | $31.88 > 0.50$ | OK | |
| $n_c(f_0) > 200$ | $26775.0 > 200$ | OK | |
| $\sigma_A(f) < 2$ for $0.5f_0 < f < 2f_0$ if $f_0 > 0.5\text{Hz}$ $\sigma_A(f) < 3$ for $0.5f_0 < f < 2f_0$ if $f_0 < 0.5\text{Hz}$ | Exceeded 0 out of 1531 times | OK | |

Criteria for a clear H/V peak



[At least 5 out of 6 should be fulfilled]

| | | | |
|---|---------------------|----|----|
| Exists f^- in $[f_0/4, f_0]$ $A_{H/V}(f^-) < A_0 / 2$ | | | NO |
| Exists f^+ in $[f_0, 4f_0]$ $A_{H/V}(f^+) < A_0 / 2$ | | | NO |
| $A_0 > 2$ | $2.80 > 2$ | OK | |
| $f_{\text{peak}}[A_{H/V}(f) \pm \sigma_A(f)] = f_0 \pm 5\%$ | $ 0.1027 < 0.05$ | | NO |
| $\sigma_f < \varepsilon(f_0)$ | $3.27358 < 1.59375$ | | NO |
| $\sigma_A(f_0) < \theta(f_0)$ | $0.2142 < 1.58$ | OK | |

| | |
|------------------------|---|
| L_w | window length |
| n_w | number of windows used in the analysis |
| $n_c = L_w n_w f_0$ | number of significant cycles |
| f | current frequency |
| f_0 | H/V peak frequency |
| σ_f | standard deviation of H/V peak frequency |
| $\varepsilon(f_0)$ | threshold value for the stability condition $\sigma_f < \varepsilon(f_0)$ |
| A_0 | H/V peak amplitude at frequency f_0 |
| $A_{H/V}(f)$ | H/V curve amplitude at frequency f |
| f^- | frequency between $f_0/4$ and f_0 for which $A_{H/V}(f^-) < A_0/2$ |
| f^+ | frequency between f_0 and $4f_0$ for which $A_{H/V}(f^+) < A_0/2$ |
| $\sigma_A(f)$ | standard deviation of $A_{H/V}(f)$, $\sigma_A(f)$ is the factor by which the mean $A_{H/V}(f)$ curve should be multiplied or divided |
| $\sigma_{\log H/V}(f)$ | standard deviation of $\log A_{H/V}(f)$ curve |
| $\theta(f_0)$ | threshold value for the stability condition $\sigma_A(f) < \theta(f_0)$ |


Threshold values for σ_f and $\sigma_A(f_0)$

| Freq. range [Hz] | < 0.2 | 0.2 – 0.5 | 0.5 – 1.0 | 1.0 – 2.0 | > 2.0 |
|---|------------|-----------|------------|------------|------------|
| $\varepsilon(f_0)$ [Hz] | $0.25 f_0$ | $0.2 f_0$ | $0.15 f_0$ | $0.10 f_0$ | $0.05 f_0$ |
| $\theta(f_0)$ for $\sigma_A(f_0)$ | 3.0 | 2.5 | 2.0 | 1.78 | 1.58 |
| $\log \theta(f_0)$ for $\sigma_{\log H/V}(f_0)$ | 0.48 | 0.40 | 0.30 | 0.25 | 0.20 |



POGGIO SAN VICINO – MASW3

Shot at (48, 0, 0), time=2017-10-04 00:00:00



Fundamental mode

